

ROPAC® MP 10 LH
UN Certified
for dangerous solid goods



Schoeller Allibert



Technical Data Sheet

PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 10 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	268 mm
Height incl. lid	274 mm
Closing system	Press-on lid with tear-off band
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load : 140 kg/ 24 h/23°C
Option	---



PAIL CHARACTERISTICS – REFERENCE 7510006

Volume brim full	12,0 l (3.17 US gallons)
Volume under lid	11,3 l (2.98 US gallons)
UN certified for a maximum weight of content	14 kg
Weight with handle	492,1 gr
Internal diameter at top	252 mm
Embossing	Ⓡ 1H2/Y14/S/--/F/BVT 26086
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	264 pails (12 piles of 22 pails)
Height of pallet	1,87 m




LID CHARACTERISTICS – REFERENCE 7538020

Weight without gasket	135 g
Diameter	250 mm
Embossing	Ⓡ MP-10H
Gasket	PVC
Standard palletisation (800x1200 NIMP15)	1056 lids (12 piles of 88 lids)
Height of pallet	1,75 m



These specifications are without legal warranty and subject to changes without notification.

September 2018/ SV



SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11

Info.switzerland@schoellerallibert.com
www.ropac-packaging.com