

ROPAC® MP 32 LH – 36 kg
UN Certified
for dangerous solid goods



Schoeller Allibert



Technical Data Sheet

PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 32LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	379 mm
Height incl. lid	405 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	1,84 cm ³ / day for 21% oxygen
UN certified for	II and III (group b and c of each class except 1 & 2)
Packaging classification	Dangerous solid goods (class Y and Z)
Handling	Hand grips
Raw material	HDPE
Stackability	UN load: 234 kg/24h/23°C
Option	---



PAIL CHARACTERISTICS – REFERENCE 7526006

Volume brim full	34,4 l (9.09 US gallons)
Volume under lid	32,5 l (8.58 US gallons)
UN certified for a maximum weight of content	36 kg
Weight	1070 g
Internal diameter at top	357,5 mm
Embossing	① 1H2/Y36/--/F/BVT 260833
Decoration type	---
Decoration area	---
Standard palletisation (800x1200 NIMP15)	150 pails (6 piles of 25 pails)
Height of pallet	1,75 m




LID CHARACTERISTICS – REFERENCE 7551030

Weight without gasket	330 g
Diameter	355 mm
Embossing	ROPAC® 32S
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	300 lids (6 piles of 50 lids)
Height of pallet	1,85 m



These specifications are without legal warranty and subject to changes without notification.

September 2018/ SV



SCHOELLER ALLIBERT SWISS Sàrl
 11, route de la Condémine
 CH-1680 ROMONT
 Tel. +41 26 651 92 11

Info.switzerland@schoellerallibert.com
www.ropac-packaging.com