



Schoeller Allibert



PREMIUM  
PACKAGING  
PROTECTION

# ROPAC® MP 5 LH

## UN Certified

### for dangerous solid goods

## Technical Data Sheet

#### PACKAGING DESCRIPTION – RANGE SECURE

Commercial reference	ROPAC® MP 5 LH
Shape	Conical
Packaging type (following ADR)	1H2
Reference	ADR, RID, ADN, IMDG-Code, DOC OACI 9284 AN 905
External diameter at top	217 mm
Height incl. lid	219 mm
Closing system	Press-on lid with tear-off band
Oxygen permeability (following ASTM D 3985)	0,70 cm <sup>3</sup> /day for 21% oxygen
UN certified for	II and III (group b and c of each class, excepted 1 and 2).
Packaging classification	Dangerous solid goods
Handling	Plastic handle
Raw material	HDPE
Stackability	UN load: 78kg/24h/23°C
Option	Flex-spout on request



#### PAIL CHARACTERISTICS – REFERENCE 7505006

Volume brim full	5,9 l (1.56 US gallon)
Volume under lid	5,5 l (1.45 US gallon)
UN certified for a maximum weight of content	6 kg
Weight with handle	305,35 g
Internal diameter at top	200,5 mm
Embossing	Ⓢ 1H2/Y6/S/--/F/BVT260829
Decoration type	Digital print
Decoration area	On request
Standard palletisation (800x1200 NIMP15)	540 pieces (18 piles of 30 pieces)
Height of pallet	1,91 m



#### LID CHARACTERISTICS – REFERENCE 7536030

Weight without gasket	91 g
Diameter	202 mm
Embossing	Ⓢ MP3-6 H
Gasket	SEBS
Standard palletisation (800x1200 NIMP15)	1620 pieces with or without flex-spout (6 boxes of 270 pcs)
Height of pallet	2,02 m



These specifications are without legal warranty and subject to changes without notification.

November 2018 / SV

SCHOELLER ALLIBERT SWISS Sàrl  
11, route de la Condémine  
CH-1680 ROMONT  
Tel. +41 26 651 92 11

[Info.switzerland@schoellerallibert.com](mailto:Info.switzerland@schoellerallibert.com)  
[www.ropac-packaging.com](http://www.ropac-packaging.com)

