

# ECOBULK MX 560

Compact design for the highest flexibility at full performance.



**Benefit from the highest SCHÜTZ quality and the additional flexibility offered by our ECOBULK MX 560:**

- Optimum filling volume with a lower container height and simultaneous use of the proven pallets from our 1,000 and 1,250 litre models with the dimension of 1,200 x 1,000 mm
- Perfect use of storage and transport space – including in ISO containers thanks to optimum pallet size
- Superior stability of the steel cage due to four horizontal tubes
- Ideal for mobile use, e.g. in agriculture/agrochemistry
- Safe and highly efficient packaging solution for all applications and uses where smaller container sizes are beneficial
- Easier handling due to lower container weight in filled and unfilled state
- Large 8-field label plate for detailed product labelling

In case of technical concerns or questions: [tcs@schuetz.net](mailto:tcs@schuetz.net)

**SCHÜTZ**  
PACKAGING SYSTEMS

[www.schuetz.net](http://www.schuetz.net)

## Material

### Inner bottle

Extrusion blow-moulded HDPE  
EVOH permeation barrier (optional)

### Outer container

Welded tubular steel grid, galvanized

### Bottom plate

Made of steel to provide stability and to facilitate minimum residual contents from the inner container

## Pallets (4-way entry)



## Certifications

### UN 31 HA1/Y (optional)

Maximum density 1.9 g/cm<sup>3</sup>

### Suitable for use in ex-zones 1 and 2 (optional)

Tested for electrostatic safety (optional)

### SCHÜTZ FOODCERT (optional)

System certification for food (contains materials that are FDA compliant)

### SCHÜTZ CLEANCERT (optional)

For highest safety and technical cleanliness

## Capacity

### MX 560

560 litres (150 gal)

## Outlet valves

Integrated butterfly valve DN 50

Integrated ball valve DN 50

## Filling opening


DN 150 with screw cap

## Plug (optional)

G2-BreatherPlus plug with aeration membrane and deaeration vent


## Check valve (optional)

Check valve to prevent backflow of filling product into the container



## ISO container loading

3-high throughout, a total of 30 units per 20' container



## Dimensions (mm)


1,200 x 1,000 x 750 (L x W x H)

## Weight

44 kg with steel pallet  
48 kg with plastic skid pallet  
49 kg with full-plastic pallet

## Dynamic load

Filled ECOBULK according to the specific weight of the filling goods



## Static load

Max. 5-high

